



### 优势

- 圆弧状滤褶
- 防水硬纸板
- 低阻力
- 低能耗

应用	空调箱的预过滤器
外框	刚性防水纸板
滤材	棉/复合纤维
尺寸	过滤器截面尺寸(EN15805)
最大风量	1,25 x 额定风量
最高温度(°C)	70°C
最大相对湿度	100%
安装选项	可选正面压紧或侧面抽拉式的安装框架



料号	类型	EN779	ISO16890	尺寸 WxHxD (mm)	风量/初阻力 (m³/h/Pa)	重量(kg)
049880005LM	AeroPleat Eco 24x24x2	G4	Coarse 65%	595x595x45	3200/70	0,7
049880006LM	AeroPleat Eco 24x12x2	G4	Coarse 65%	290x595x45	1500/70	0,3
059413002LM	AeroPleat Eco 24x12x4	G4	Coarse 65%	290x595x95	1800/70	0,7
059413001LM	AeroPleat Eco 24x24x4	G4	Coarse 65%	594x594x95	3400/65	1.45
049880012LM	AeroPleat Eco 24x20x2	G4	Coarse 65%	594x495x45	2840/70	0.45
059413008LM	AeroPleat Eco 24x20x4	G4	Coarse 65%	594x495x95	2840/65	0.45
054862051LM	AeroPleat Eco 24x24x1	G4	Coarse 65%	594x594x22	2380/250	0.6
054862061LM	AeroPleat Eco 24x20x1	G4	Coarse 65%	594x495x22	1990/250	0.53
054862054LM	AeroPleat Eco 24x12x1	G4	Coarse 65%	594x289x22	1190/250	0.3