



优势

- 结构坚固
- 与外壳粘合，以消除空气旁路
- 防水硬纸板

外框	纸板
滤材	棉/复合纤维
尺寸	过滤器截面尺寸(EN15805)
推荐终阻力	250 Pa
最大风量	1,25 x 额定风量
最高温度(°C)	70°C
最大相对湿度	100%
安装选项	可选正面压紧或侧面抽拉式的安装框架



料号	类型	EN779	ASHRAE 52.2-2017	ISO16890	尺寸 WxHxD (mm)	风量/初阻力 (m³/h/Pa)	重量 (kg)
05001003C	Aeropleat III 20x16x2	G4	MERV 8	Coarse 65%	394x495x44	1887/70	0.4
05001004C	Aeropleat III 20x20x2	G4	MERV 8	Coarse 65%	495x495x44	2363/70	0.5
05001005C	Aeropleat III 25x20x2	G4	MERV 8	Coarse 65%	495x622x44	2950/70	0.6
05001006C	Aeropleat III 25x16x2	G4	MERV 8	Coarse 65%	394x622x44	2363/70	0.5
05001001C	Aeropleat III 24x24x2	G4	MERV 8	Coarse 65%	594x594x44	3400/70	0.65
05001002C	Aeropleat III 24x12x2	G4	MERV 8	Coarse 65%	289x594x44	1656/70	0.35
05001011C	Aeropleat III 24x20x2	G4	MERV 8	Coarse 65%	495x594x44	2839/70	0.55
05002001C	Aeropleat III 24x24x4	G4	MERV 8	Coarse 65%	594x594x95	3400/50	1.2
05002002C	Aeropleat III 24x12x4	G4	MERV 8	Coarse 65%	289x594x95	1700/50	0.65
05002004C	Aeropleat III 20x16x4	G4	MERV 8	Coarse 65%	390x492x95	1853/50	0.75
05002010C	Aeropleat III 25x16x4	G4	MERV 8	Coarse 65%	390x619x95	2332/50	0.9
05002006C	Aeropleat III 24x20x4	G4	MERV 8	Coarse 65%	492x594x95	2768/50	1.05
05002003C	Aeropleat III 20x20x4	G4	MERV 8	Coarse 65%	492x492x95	2336/50	0.9