



优势

- 减少更换频率
- 结构紧凑、重量轻
- 滤料面积大
- 寿命长

应用	通过滤单元及通风系统的预过滤器
外框	ABS
滤材	玻璃纤维
分隔物	热熔胶
尺寸	过滤器截面尺寸(EN15805)
最大终阻力	350 Pa
最大风量	1,1 x 额定风量
最高温度 (°C)	70°C
最大相对湿度	100%
安装选项	可选正面压紧或侧面抽拉式的安装框架



料号	类型	EN779	ISO16890	尺寸 WxHxD (mm)	风量/初阻力 (m³/h/Pa)	重量 (kg)	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
23465572C	3GPPS-12242-M5(287x592x48)	M5	ePM10 60%	592x287x48	1450/65	1,5					
23664409C	3GPPS-24242-M5(592x592x48)	M5	ePM10 60%	592x592x48	2900/65	3	15	15	24	24	64
23465500C	3GPPS-24242-M6(592x592x48)	M6	ePM10 70%	592x592x48	2900/75	3	26	25	42	40	74
23465200C	3GPPS-12242-M6(287x592x48)	M6	ePM10 70%	592x287x48	1450/75	1,5					
23675200C	3GPPS-12242-F7(287x592x48)	F7	ePM1 55%	287x592x48	1450/110	1,5					
23675500C	3GPPS-24242-F7(592x592x48)	F7	ePM1 55%	592x592x48	2900/110	3	55	55	65	65	85
23685200C	3GPPS-12242-F8(287x592x48)	F8	ePM1 70%	287x592x48	1450/160	1,5					
23485500C	3GPPS-24242-F8(592x592x48)	F8	ePM1 70%	592x592x48	2900/160	3	74	74	85	85	94
23765200C	3GPPS-12244-M6(287x592x96)	M6	ePM10 70%	287x592x96	1450/70	3					
23765500C	3GPPS-24244-M6(592x592x96)	M6	ePM10 70%	592x592x96	2900/70	4	26	25	42	40	74
23775200C	3GPPS-12244-F7(287x592x96)	F7	ePM1 55%	287x592x96	1450/100	3					
23775500C	3GPPS-24244-F7(592x592x96)	F7	ePM1 55%	592x592x96	2900/100	4	55	55	65	65	85
23785200C	3GPPS-12244-F8(287x592x96)	F8	ePM1 70%	287x592x96	1450/105	3					
23785500C	3GPPS-24244-F8(592x592x96)	F8	ePM1 70%	592x592x96	2900/105	4	74	74	85	85	94