



优势

- 金属框架、稳定牢固
- 可根据客户需要定制非标尺寸
- 大容尘量
- 锥型袋口, 优化气流阻力

应用	舒适空调系统, 预过滤器应用
外框	镀锌钢
滤材	玻璃纤维
尺寸	过滤器截面尺寸(EN15805)
最大风量	1,25 x 额定风量
最高温度(°C)	70°C
最大相对湿度	100%
安装选项	可选正面压紧或侧面抽拉式的安装框架



料号	类型	EN779	ISO16890	尺寸 WxHxD (mm)	风量/初阻力 (m³/h/Pa)	袋数	重量(kg)	能耗	能耗等级	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
3140085CN	A5	M5	ePM10 60%	592x592x600	3400/45	6	1.9	748	C	15	15	27	27	64
3140086CN	B5	M5	ePM10 60%	490x592x600	2800/45	5	1.6		C					
3140087CN	C5	M5	ePM10 60%	287x592x600	1700/45	3	1.1		C					
3140017CN	A6	M6	ePM2,5 50%	592x592x600	3400/70	6	1.9	1189	C	40	40	54	54	80
3140018CN	B6	M6	ePM2,5 50%	490x592x600	2800/70	5	1,6		C					
3140019CN	C6	M6	ePM2,5 50%	287x592x600	1700/70	3	1,1		C					
3140013CN	UF6	M6	ePM2,5 50%	592x592x600	3400/60	8	2,9	872	B	40	40	54	54	80
3140014CN	UG6	M6	ePM2,5 50%	490x592x600	2800/60	6	2,4		B					
3140015CN	UH6	M6	ePM2,5 50%	287x592x600	1700/60	4	1,5		B					
3140042CN	UG7 ES	F7	ePM1 60%	490x592x600	2800/75	6	2,4		A					
3140043CN	UH7 ES	F7	ePM1 60%	287x592x600	1700/75	4	1,5		A					
3140041CN	UF7 ES	F7	ePM1 60%	592x592x600	3400/75	8	2.9	940	A	62	62	71	71	90
3140045CN	A7 ES	F7	ePM1 60%	592x592x600	3400/95	6	1.9	1337	C	62	62	71	71	90
3140046CN	B7 ES	F7	ePM1 60%	490x592x600	2800/95	5	1.6		C					
3140047CN	C7 ES	F7	ePM1 60%	287x592x600	1700/95	3	1.1		C					
3140069CN	UF8	F8	ePM1 70%	592x592x600	3400/160	8	2.19							
3140070CN	UG8	F8	ePM1 70%	490x592x600	2800/160	6	1.8							
3140070CN	UH8	F8	ePM1 70%	287x592x600	1700/160	4	1.32							
3145012CN	UF9	F9	ePM1 85%	592x592x600	3400/160	8	2,9	1956	D	87	87	91	91	98
3145013CN	UG9	F9	ePM1 85%	490x592x600	2800/160	6	2,4		D					
3145014CN	UH9	F9	ePM1 85%	287x592x600	1700/160	4	1,5		D					

最低能耗, kWh/year: 参考欧洲准则 4/21-2019

能耗标准: 参考欧洲RS 4/C/001-2019